

Seismic Data Channel

1C

ADC Resolution

24 bit Delta Sigma

Sample Interval

0.25ms, 0.5ms, 1ms, 2ms, 4ms

Preamplifier Gain

Programmable 0dB to 42dB in 6dB steps

Anti-alias Filter

- 206.5Hz @2ms, 413 Hz @1ms
- Linear Phase or Minimum Phase

Low Cut Filter

None

Operating Temperature Range

-40° C to +75° C

Operational Autonomy

- 1,080 Hours
- 12 Hours per day: 90 days
- 24 Hours per day: 45 days

Weight

810 g

Dimensions

6.9 cm x 20.9 cm

Battery

- 13.4 Ah Li-Ion
- Charge Temperature Range: 0° C ~ +45° C
- Cycle Life: >500 cycles to 80%

Acquisition Channel

@2ms sample interval, 25°C, 31.25 Hz

- Maximum input signal: 1768 mVrms @0dB
- Total Harmonic Distortion: 0.0001% @31.25Hz
- Instantaneous Dynamic Range: 127dB @2ms
- System Dynamic Range: 148dB
- Equivalent Input Noise:
 - 1500 nV @0dB
 - 400 nV @12dB
 - 160 nV @24dB
- Gain Accuracy: 0.25% unit to unit
- Input Impedance: 100k Ohm
- Timing Accuracy: +/- 12.5µsec customizable at client request

Instrument Test

Internal Noise, Total Harmonic Distortion, Impulse Response

Sensor Test

Resistance, Impedance, Noise

Sensor

- Internal, Single Geophone
 - 5Hz or 10 Hz +/- 3.5%
 - 85.8 V/m/s +/- 3.5%
- Other geophones available upon request

Memory

8 GB standard (expandable to 64 GB)



NRU EL™

Learn More at geophysicaltechnology.com

